



# Shell Rimula R5 E 10W-40 (CI-4/228.3)

Rimula R5 E Energised Protection



Shell Rimula R5 E  
 Shell Rimula R5 E  
 Rimula R5 E  
 US 2002, Euro 3  
 Shell Rimula R5 E  
 Rimula R5 E

&

Shell Rimula R5 E  
 Euro 2, 3, US 2002  
 (DPF)  
 LMLME.

Rimula R6

- Cummins: CES 20078, 77, 76, 72, 71
- MACK: EO-M, EO-M+
- MAN: 3275
- MB: 228.3
- Renault Trucks: RLD-2
- Volvo: VDS-3, VDS-2
- API: CI-4, CH-4, CG-4, CF-4, CF.
- ACEA: E7, E5, E3
- Global DHD-1



Rimula R5 E

Shell

Properties			Method	Shell Rimula R5 E 10W-40 (CI-4/228.3)
				10W-40
	@40°C	mm <sup>2</sup> /s	ASTM D445	90
	@100°C	mm <sup>2</sup> /s	ASTM D445	13.4
	@-25°C	mPa s	ASTM D5293	6600
			ASTM D2270	150
(TBN)		mg KOH/g	ASTM D2896	10
		%	ASTM D874	1.2
	@15°C	kg/l	ASTM D4052	0.882
(COC)		°C	ASTM D92	220
		°C	ASTM D97	-39

Shell,

&

Shell Rimula R5 10W-40 (CI-4/228.3)

: <http://www.epc.Shell.com/>

Shell