


CASSIDA FLUID CR Series

Product Information

Synthetic compressor lubricants for food
manufacturing machinery



CASSIDA FLUID CR 32, 46, 68 and 100 are high performance fluids specially developed for use in rotary screw and vane air compressors used in the food and beverage processing and packaging industry.

They are based on a careful blend of synthetic fluids and selected additives chosen for their ability to meet the stringent requirements of the food industry.

Certified by NSF for ISO 21469 and registered by NSF (Class H1) for use where there is potential for incidental food contact. Produced according to FLT Quality Standards, in facilities where HACCP audit and Good Manufacturing Practice have been implemented and form part of the quality and hygiene management systems ISO 9001 and ISO 21469.

CERTIFICATIONS AND SPECIFICATIONS

- NSF H1
- NSF ISO 21469
- Kosher
- Halal
- DIN 51506 VBL, VCL, VDL
- ISO 6743-3 DAG, DAH, DAJ



PERFORMANCE FEATURES

- Base fluids have an ability to provide superior lubrication under the majority of operating conditions
- Very good anti-wear performance resulting in greater plant utilisation
- CASSIDA FLUID CR has inherently good water shedding properties and resistance to foaming
- Excellent high temperature performance resists the formation of harmful products of oxidation at elevated temperatures, resulting in long oil life
- Neutral odour and taste
- High viscosity index
- Good protection against corrosion of all metal working surfaces
- Good low temperature properties down to -40 °C

These products have demonstrated similar performance to conventional compressor lubricants in rotary air compressors operating at normal temperatures, e.g. up to +100 °C. It is strongly recommended that a used oil and/or equipment condition monitoring service be employed for extended periods of operation in excess of the pump manufacturers' recommended oil change intervals.

SEAL AND PAINT COMPATIBILITY

Compatible with the elastomers, gaskets, seals and paints normally used in food machinery lubrication systems.

HANDLING AND STORAGE


All food grade lubricants should be stored separately from other lubricants, chemical substances and foodstuffs and out of direct sunlight or other heat sources. Store between 0 °C and +40 °C. Provided that the product has been stored under these conditions we recommend to use the product within 5 years from the date of manufacture. Upon opening a pack, the product must be used within 2 years (or within 5 years of date of manufacture, whichever is the sooner).

APPLICATIONS

- Screw and vane compressors
- Piston Compressors (ISO VG 100)
- Plain and anti-friction bearings
- General purpose lubrication including light duty gearboxes

TYPICAL CHARACTERISTICS (Typical for current production. Variations in these characteristics may occur.)

			CASSIDA FLUID CR			
			32	46	68	100
Property		Test Method				
NSF Reg. No.			144684	144685	144686	144687
Colour			Pale yellow			
Density at +15 °C	kg/m ³	ISO 12185	836	838	843	846
Flashpoint	°C	ISO 2592	247	252	256	258
Pourpoint	°C	ISO 3016	-57	-57	-57	-54
Kin. Visc. at +40 °C	mm ² /s	ISO 3104	32	46	68	100
Kin. Visc. at +100 °C	mm ² /s	ISO 3104	6.14	7,88	10,9	14,6
Viscosity index		ISO 2909	143	142	151	151
Demulsibility at +54 °C	min.	ISO 6614	5	15	15	20 (+82 °C)



FUCHS LUBRITECH GMBH
 Werner-Heisenberg-Straße 1
 67661 Kaiserslautern / Germany
 T: +49 (0) 6301 3206-0 / F: +49 (0) 6301 3206-940
www.fuchs-lubritech.com

 A Member of the
 FUCHS PETROLUB Group

As far as we know these information reflect the current state of knowledge and our research. They cannot, however, be taken as an assurance about the properties nor as a guarantee of the suitability of the product for the individual case in point. Before using our products the purchaser must, therefore, check the suitability and be satisfied that the output will be satisfactory. Our products are continually being up-dated. We reserve the right, therefore, to alter the information of this product information at any time and without prior announcement. We are specialized in developing products for extreme tribological problems in cooperation with end users. FUCHS LUBRITECH provides service and individual advice. Please contact us! E-Mail: cassida.lubricants@fuchs-lubritech.de